

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

| | | | |
|---|--|--|--|
| (51) International Patent Classification ⁶ : G06F 13/00, 17/30, 3/00 | | A1 | (11) International Publication Number: WO 97/23831 |
| | | | (43) International Publication Date: 3 July 1997 (03.07.97) |
| (21) International Application Number: PCT/US96/20104 | | (74) Agents: TAYLOR, Edwin, H. et al.; Blakely, Sokoloff, Taylor & Zafman, L.L.P., 7th floor, 12400 Wilshire Boulevard, Los Angeles, CA 90025-1026 (US). | |
| (22) International Filing Date: 20 December 1996 (20.12.96) | | | |
| (30) Priority Data: 08/577,875 22 December 1995 (22.12.95) US | | (81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). | |
| (71) Applicant (for all designated States except US): INTEL CORPORATION [US/US]; 2200 Mission College Boulevard, Santa Clara, CA 95052 (US). | | | |
| (72) Inventors; and | | | |
| (75) Inventors/Applicants (for US only): HAMNER, John, F. [US/US]; 520 N. 1370 W., Pleasant Grove, UT 84062 (US). JANICH, Sandra [US/US]; 4754 Idlewild, Salt Lake City, UT 84124 (US). DESPAIN, Jeffrey, L. [US/US]; 805 N. 400 East, Pleasant Grove, UT 84062 (US). NIEMANN, Katherine, D. [US/US]; 1166 West 250 South, Orem, UT 84058 (US). SEVY, Brian, D. [US/US]; 2340 North 1000 East, Lehi, UT 84043 (US). TRAN, Dzung, D. [US/US]; 738 South West-17th Place, Beaverton, OR 97006 (US). WELCH, Frank, K. [US/US]; 1508 S.W. 19th Avenue, Portland, OR 97201 (US). | | Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments. | |

(54) Title: METHOD AND APPARATUS FOR MANAGING A COMPUTER NETWORK



(57) Abstract

A computer-implemented method of managing a computer network including a plurality of devices is provided, wherein a plurality of network management tasks are performable upon the devices. Data is gathered about a present configuration of the network, including the types of devices in the network, the quantity of each type of device present in the network, the relationships between the devices, and the tasks performable upon each of the devices. The data is then stored in a database representing a network map. A display is generated corresponding to the network map using the data in the database (200). The display shows an association of the devices (201) with the tasks performable on the devices (202) using bitmap representations (205, 207) of the devices and tasks. The display may include hierarchical, schematic, or geographical representations of the devices on the network (201). The devices are organized into a plurality of groups. In response to a user input selecting a device or group, the tasks performable by that device or group are identified on the display (209, 211). A user may initiate any one of the displayed tasks by applying a user input selecting that task.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

| | | | | | |
|----|--------------------------|----|---------------------------------------|----|--------------------------|
| AM | Armenia | GB | United Kingdom | MW | Malawi |
| AT | Austria | GE | Georgia | MX | Mexico |
| AU | Australia | GN | Guinea | NE | Niger |
| BB | Barbados | GR | Greece | NL | Netherlands |
| BE | Belgium | HU | Hungary | NO | Norway |
| BF | Burkina Faso | IE | Ireland | NZ | New Zealand |
| BG | Bulgaria | IT | Italy | PL | Poland |
| BJ | Benin | JP | Japan | PT | Portugal |
| BR | Brazil | KE | Kenya | RO | Romania |
| BY | Belarus | KG | Kyrgyzstan | RU | Russian Federation |
| CA | Canada | KP | Democratic People's Republic of Korea | SD | Sudan |
| CF | Central African Republic | KR | Republic of Korea | SE | Sweden |
| CG | Congo | KZ | Kazakhstan | SG | Singapore |
| CH | Switzerland | LI | Liechtenstein | SI | Slovenia |
| CI | Côte d'Ivoire | LK | Sri Lanka | SK | Slovakia |
| CM | Cameroon | LR | Liberia | SN | Senegal |
| CN | China | LT | Lithuania | SZ | Swaziland |
| CS | Czechoslovakia | LU | Luxembourg | TD | Chad |
| CZ | Czech Republic | LV | Latvia | TG | Togo |
| DE | Germany | MC | Monaco | TJ | Tajikistan |
| DK | Denmark | MD | Republic of Moldova | TT | Trinidad and Tobago |
| EE | Estonia | MG | Madagascar | UA | Ukraine |
| ES | Spain | ML | Mali | UG | Uganda |
| FI | Finland | MN | Mongolia | US | United States of America |
| FR | France | MR | Mauritania | UZ | Uzbekistan |
| GA | Gabon | | | VN | Viet Nam |

Method and Apparatus for Managing a Computer Network

FIELD OF THE INVENTION

The present invention pertains to the field of computer networking. More particularly, the present invention relates to tools for providing management services for a computer network.

BACKGROUND OF THE INVENTION

The rapidly increasing use of personal computers has created a growing interest worldwide in computer networking, a prime example of which is the pervasive use of "the Internet". Computer networking on a smaller scale, such as in the form of Local Area Networks (LANs), has also expanded into countless different areas of business and technology. As users place more reliance upon computer networks, however, they also demand more sophisticated capabilities for managing these networks. Various different software packages exist for providing users with such capabilities.

Existing software products for network management have several disadvantages, however. For example, such products tend to be largely "tool-based". That is, although the software provides the user (e.g., a network administrator) with a set of tools for performing network functions, such as troubleshooting, it is often up to the user to determine which tool is best for performing a particular task and to determine on which devices in the network a task should be performed. Further, it is often difficult for a network administrator or user to become proficient enough with the available management

tools to be able to use those tools to their full potential. These tools also tend to require that the user have extensive knowledge about the layout of the network, and that the user provide this information to the management tool. Moreover, existing network management tools generally provide the user with only one or two predetermined formats for examining the layout of the network.

Hence, what is needed is a set of network management services which are designed from a more flexible, device-oriented perspective. Specifically, what is needed is a network management tool which provides the user with information on the layout of the network, tasks that can be performed, and the devices on which each particular task can be performed. What is further needed is a tool which provides the user with customizable ways of viewing the layout of the network.

SUMMARY OF THE INVENTION

A computer-implemented method of providing information on a computer network is provided. The network includes a number of devices. A number of tasks are provided, such that each task can be performed upon at least one of the devices. In the method, a display is generated having a first area corresponding to the devices and a second area corresponding to the tasks. A representation of a subset of the plurality of devices is displayed in the first area. A user input selecting the representation is accepted, and, in response to the user

input, information indicating which of the tasks can be performed upon each device of the subset is displayed in the second area.

Other features of the present invention will be apparent from the accompanying drawings and from the detailed description which follows.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is illustrated by way of example and not limitation in the figures of the accompanying drawings, in which like references indicate similar elements and in which:

Figure 1 illustrates a computer network in which the present invention can be implemented.

Figure 2A illustrates a logical view display having a device window and a task window.

Figure 2B illustrates a display consisting of a tree hierarchy of devices.

Figure 3 is a block diagram of core services for managing a network.

Figure 4 is a block diagram of a discovery manager core service.

Figure 5 is an object relationship model (ORM) diagram showing a metaschema of a database engine according to the present invention.

Figure 6 is a block diagram of a physical network model core service.

Figure 7 is an object relationship model (ORM) diagram of a physical network model schema.

Figure 8 illustrates a graph representing network configuration information stored in accordance with the present invention.

Figure 9 is a block diagram of a view generator core service.

Figure 10 is a flowchart depicting the overall operation of core services for managing a network in accordance with the present invention.

Figure 11 is a flowchart depicting the steps performed during the network discovery process by core services in accordance with the present invention.

Figure 12 is a flowchart illustrating the steps for calculating the tasks for a selected device or group.

Figure 13 is a flowchart illustrating the steps for calculating tasks for a group.

Figure 14 is a flowchart illustrating the steps for calculating the tasks for a given device.

Figure 15 is a flowchart illustrating the steps for calculating tasks of a component.

DETAILED DESCRIPTION

A method and apparatus for providing management services for a computer network is described. In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the present invention.

It will be evident, however, to one skilled in the art that the present invention may be practiced without these specific details. In other instances, well-known structures and devices are shown in block diagram form in order to avoid unnecessarily obscuring the present invention.

The present invention includes steps for providing a number of core services for managing a computer network, such as a local area network (LAN). The steps may be performed by a general purpose processor programmed with instructions that cause the processor to perform the recited steps. The instructions may be stored in a memory or on a magnetic disk, CD-ROM, or any other mass storage device. Alternatively, the steps may be performed by specific hardware components that contain hard-wired logic for performing the recited steps, or by any combination of programmed general purpose computer components and custom hardware components.

As illustrated in Figure 3, the core services 300 include a discovery manager 301, a database engine 302, a physical network model 303, a view generator 304, and a task manager 305. The core services 300 provide a user, such as a LAN administrator, with customizable views of the layout of a network, the various network management tasks that can be performed on devices in the network, and the particular devices on which each task can be performed. It should be noted that, for purposes of this description, the term "device" may refer to either a physical device or a logical device.

The functions and information provided by the core services 300 are presented through a graphical user interface. Accordingly, the present invention is designed to operate in a windows-and-icons environment. Specific methods for implementing a windows-and-icons environment are well known in the computer art and therefore will not be described herein. The present invention also operates in conjunction with an operating system and system functions capable of displaying windows, graphical and textural information within windows, and cursor symbols on the display device. System functions for interfacing with a mouse and cursor function keys are also required. These resources are standard processing components which are also well known in the computer art.

Figure 1 illustrates a computer network 10 in which the present invention may be implemented. The network 10 includes a number of individual computer systems 12, 15, and 20. These computer systems include personal computer (PC) systems 20 that are clients of either a management server 12 or a managed server 15. Although many servers may be present in the network 10, only one server, the management server 12, is required in order to implement the present invention. At least some of the services, including control software for coordinating the various services, are implemented within the management server 12. The managed server 15 represents any server in the network 10 other than the management server 12. It should be appreciated that, in any given network in which the present

invention is implemented, there may be multiple management servers 12 or managed servers 15.

As will be described in greater detail below, the core services gather data, either periodically or in response to a user command, about the current physical and logical layout of the network. This data, which includes the types of devices in the network, the quantity of each type of device, and their connectivity, is then stored in a database representing a network "map". In addition, the core services gather and maintain data regarding tasks which can be performed upon each of the devices. Tasks are actions that can be taken to troubleshoot, monitor, or report on devices in the network. Some examples of tasks which might be performed on various devices in a network are: viewing the screen of a particular PC; displaying packet counts; running a report; executing a remote virus scan; rebooting selected workstations; displaying print jobs; or, displaying non-functioning printers.

A display, referred to in this description as the "logical view", shows symbolically the devices in the network and associated performable tasks. In one embodiment, the devices are shown as part of a hierarchical structure based on the stored network map. Devices can be organized into various device groups, which are user-definable, and tasks can be organized into various user-definable task categories, which are also user-definable. The user may initiate any of the displayed tasks by applying a user input via a "control panel" screen (e.g., by double-clicking on a task icon with a mouse).

I. User Interface

Figure 2A illustrates an example of a logical view 200 display for a typical network. The logical view 200 includes a device window 201 and a task window 202. Devices and device groups in the network are represented in the device window 201. Each group and each device is represented with its name and a bitmap (icon). For example, device window 201 includes bitmaps 205, 207, and 208 representing the "PC" group, the "Printer" device group, and the "Server" device group, respectively. Double-clicking on a group bitmap with a cursor control device (e.g., a mouse, trackball, etc.) will cause that group to be expanded in the device window 201 into a tree hierarchy consisting of all devices within that group. For example, "Guest" 206 and "User 1" 210 are displayed descending from "PC" 205, because those devices are members of the "PC" group.

The task window 202 displays the tasks and categories of tasks that can be performed on a particular device or group which has been selected in the device window 201. For example, the tasks and task categories displayed in task window 202 represent tasks/categories that can be performed upon the device "User 1", the bitmap 206 of which has been selected (and is therefore enclosed by a box) within the device window 201. In the task window 202, tasks 211, 212, and 213 ("Display packet counts", "Filter on selected IPX protocol devices", and "Show print jobs belonging to selected user", respectively) each are members of the task category "Monitor" 209. Selecting a different device or group in the device window 201 will cause a different set of

tasks/categories to be displayed corresponding to the selected device or group.

The user can cause any displayed task to be performed upon a device. A task is initiated by the user's selecting the bitmaps of the desired task and the device or group upon which the task is to be performed, and then entering a predetermined user input, such as selecting an option from a pull-down menu, or double-clicking with the cursor control device on one of the tasks.

In one embodiment of the present invention, the device window 201 displays a tree hierarchy showing the logical or physical connection of all devices in the network, organized into device groups. Figure 2B shows an example of a display consisting of a tree hierarchy of devices, as represented by their bitmaps and names. Each of the devices belongs to the group "Server". The group "Server" includes a device "Server 1". Devices "NIC" (Network Interface Card) and "USER Agent" are components of the device "Server 1" and are therefore displayed with their names enclosed by the symbols "< >". Devices "GUEST", "SUPERVISOR", "User 1", and "User 2" are attached to (but not components of) device "Server 1". A second "NIC" is a component of device "User 2". It should be appreciated that alternative embodiments of the present invention might include schematic, geographic, or other views of the layout of the network, in addition to or instead of a tree hierarchy view.

II. System Architecture

As illustrated in Figure 3, the software of the present invention comprises several core services 300 implemented as distinct modules, which include a discovery manager 301, a database engine 302, a physical network model 303, a view generator 304, and a task manager 305. In general, the discovery manager 301 gathers real-time data about the devices in the managed network 10 and coordinates access to both historical network data and the real-time device data. The database engine 302 provides a logical database structure for storage of network device and task data. The database engine 302 also supports a query mechanism adequate for the needs of various client software applications, such as an inventory management application. Further, the database engine 302 allows client applications to define fields to be stored in a way that is appropriate for each such application. The physical network model 303 includes the actual database and uses the database engine 302 to provide storage and retrieval of network device information for the discovery manager 301. The physical network model 303 represents all known pieces of the managed network 10 and how those pieces interrelate. In some embodiments of the present invention, the physical network model 303 may provide means for client applications to add, modify, and remove devices and the relationships between devices, and provide, in response to a user request, lists of devices with a given relationship to a device or other list of devices. The view generator 304 provides a flexible, user-defined listing of devices in the network 10 and available tasks, which

may be displayed in the logical view 200. The LAN Administrator can arrange devices in different ways to provide the most useful presentation of network organization. Finally, the task manager 305 maintains knowledge of all executable tasks in the network and the devices on which such tasks can be performed and initiates tasks in response to user commands.

The overall operation of the core services 300 is illustrated in the flowchart of Figure 10. The discovery manager 301 determines, either periodically or in response to a user query, the logical (and, optionally, the physical) configuration of the network (step 1001) and stores this configuration information in the database of the physical network model 303. The task manager 305 determines the valid tasks for the network (i.e., tasks that are performable on at least one device in the network) (step 1002) and associates each valid task with the particular devices and groups of devices on which each such task can be performed (step 1003). If a display is requested by the user (step 1004), the logical view 200 is updated and displayed (step 1005) by the view generator 304. The process is then repeated periodically based on a user-defined update frequency (step 1006).

A. Discovery Manager

The Discovery Manager provides data on devices that are currently connected in the network as well as historical information about devices that have been connected and available in the past.

Figure 4 shows a block diagram of the discovery manager 301. The

discovery manager includes a control module 310, a number of discovery modules 312, and a discovery application programming interface (API) 311. The various discovery modules 312 poll the network 10 to find specific types of devices. Each discovery module is a specialist in finding a certain type of device, although there may be overlap in the particular devices found by different discovery modules. When a device is found by a discovery module 312, that module then adds information about the device to the physical network model 303. Referring again to Figure 1, the discovery modules 312 may be implemented on the management server 12, or they may be distributed between amongst two or more of the computers on the network 10. The presence of a module for discovering a particular type of device is recorded in a configuration file for use by the discovery control module 310.

The control module 310 and the API 311 are implemented on the management server 12. The control module 310 provides scheduling for the polling of the network performed by the discovery modules 312. The control module 310 also handles user requests for information about devices. The control module 310 can satisfy such requests by searching for devices in the physical network model 303, running one or more discovery modules 312, or both, as needed. The discovery control module 310 determines which discovery module to run by searching for entries in the configuration file that indicate the device type and the name of the corresponding discovery module to run. Thus, the network can be polled automatically by the discovery

manager 301 on a periodic basis, where the period can be user-defined, or manually in response to a user's query.

The discovery API 311 provides a functional interface between the operating system of the management server 12 and the control module 310. In the discovery API 311, any functions which return lists of devices or data about a device include a parameter which informs the discovery manager whether to look in the physical model database for the current state of the network, historical data, or both, to supply the list of devices. In either case, the devices identified will be in the database (either the devices were already present or the discovery module placed them there in response to the function being called) and applications can obtain information about them.

The functions of the discovery API 311 which can retrieve real-time data are:

- Get Device Attribute
- List Devices
- List Device Attributes
- List Devices with Attribute
- List Devices With Attribute Value
- List Linked Devices
- List Group Members

The terms "attribute", "attribute value", and the concept of "linked" devices are explained below. Other functions of the discovery API 311 include:

Add Device (to physical network model)

Update Device

Add Device to Group

List Group Members

Figure 11 provides a flowchart of the steps performed in the discovery process. Note that the responsibility for performing these steps may be distributed between various computers in the network. Based on the scheduling provided by the control module 310, the individual discovery modules 312 each poll the network for specific types of devices (steps 1101 and 1102). In order to be recognized as part of the network, a given device must provide at least the attributes belonging to a predefined set of attributes for that device type. When a particular device is found, the corresponding discovery module 312 identifies any key attribute values of that device (step 1104) and adds the device and those values to the database (step 1105).

B. Database Engine

As noted above, the database engine 302 supports a query mechanism for use by various client applications. In addition, the database engine allows client applications to define fields to be stored in an appropriate way for each such application. The database will store data efficiently even though the fields of a record are not defined until the core services 300 are actually put into use. Accordingly, the database engine 302 embodies a database schema that is used to define another, more specialized database schema. More specifically, the

database engine 302 embodies a metascema that is used to define the more-specialized schema, which is described below, that is the foundation of the physical network model 303.

Figure 5 is an object relationship model (ORM) diagram conceptually showing the components of the database engine's metascema and their relationships to each other. The primary storage unit of the database is an object 600. In the ORM diagram in Figure 5, rectangles represent object classes, lines represent relationships between objects, a diamond indicates a ternary relationship, an unfilled triangle represents the concept of specialization, and a filled triangle represents the concept of aggregation. An object 600 has an object type 601 associated with it, which is registered by the user. Each object type 602 has an object type name 602. An object 600 also has a link 603 of a specific link type 603 to another object 600. Link types 603 are registered by the user and may represent any logical connection or relationship the user wishes. Two objects 600 may have multiple links, but each link must be of a different link type 603. Each link type 603 has a link type name 603. Examples of some possible link types are: IPX (i.e., a communication protocol), physical component, logical component, and ethernet. Link records may be stored in a separate table from the object records for improved efficiency.

Attributes 605 are used for attaching data selected by the user (e.g., an device address, a mail center, etc.) to objects 600. Attributes 605 are optional fields, in that they can be used for only selected

devices. Attributes 605 are also the criteria which are used in determining if a device is recognized by the discovery manager 301 as part of the network, as will be described below. In order to be recognized as part of the network, a given device must provide at least the attributes that have been previously defined for a given device type. An attribute 605 is a specialization of an object 600. In addition, an attribute 605 is an aggregation of an attribute type 606, which is registered by the user, and an attribute value 607. Objects 600 are therefore linked to attributes 605. Each attribute type 606 has an attribute type name 608.

C. Physical Network Model

The physical network model (PNM) 303 represents all known pieces of the managed network 10 and how those pieces interrelate. Referring to Figure 6, the PNM 303 includes a PNM Manager 331, a PNM API 332 functionally coupled to the discovery manager 301, and a physical model database 333 driven by the database engine 302. The PNM 303 provides storage in the physical model database 333 of the real-time and historical network information acquired by the discovery modules 312. The stored information includes the devices, device types, device attributes, and relationships between devices in the network. Devices are represented in the physical model database 333 as objects (see Figure 4) and relationships are represented as links. The PNM 303 further provides means for client applications to add, modify, and remove devices and relationships between devices. The

PNM 303 further provides, in response to user requests, lists of devices with a specified relationship to a device or other list of devices.

To represent the physical organization of a network, the PNM 303 uses a list of all devices which have been discovered by the Discovery Manager 301 and maintains within the physical model database 333 information on how each device is connected to each other device. This connectivity information may include such information as the fact that a device is physically installed in the same box as another device, a client/server relationship, or any other connection type that could be useful to an application. The complete physical model database 333 represents a graph (i.e., a numerical model) in which the nodes in the graph represent devices and the connection between the nodes represents the connections between the devices. Standard graph theory may be used to find various relationships between nodes, such as the shortest path, cycles, connectivity, and optimization.

Figure 8 illustrates how a typical network might be stored and the various connections determined in the PNM database 333 using this approach. The network of Figure 8 includes a segment 801 and a segment 812. A segment generally represents any physically or logically contiguous part of a network. Devices which are shown (and therefore stored) as linked to a particular segment reside on that segment. In Figure 8, therefore, NIC's 802, 803, 804, and 805, NetPort 806, File Server 807, Remote Management Agent (RMA) 808, and PC 809 all reside on segment 801. Devices which reside on different

segments must be coupled by a router to communicate with each other. NIC 811 belongs to segment 812; therefore, router 810 is coupled between NIC 801 and NIC 811 in order for devices on segment 801 to communicate with devices on segment 812.

During the discovery process, device interconnections may be determined by examination of device attributes. For example, in one embodiment devices may have their segment numbers and other connection information encoded into their network addresses (which are attributes). There may be more than one connection between two nodes. In Figure 8, for example, the File Server 807 is connected to NIC 803 two times; such a connection might appear when a server is running more than one protocol stack (e.g., IPX and either TCP/IP or AppleTalk). Also, by the property of transitivity, if there is a path between two nodes, those nodes are connected and the intervening nodes can be ignored by an application, if appropriate.

Referring again to Figure 6, the PNM Manager 331 is essentially a front-end for the database. The PNM Manager 331 is responsible for properly maintaining all links and performing the queries requested of it and ensures that new nodes are inserted properly into the graph. The PNM Manager 331 can use the transitivity of the database to build lists of connected objects (e.g., which computers are connected to a particular segment).

As mentioned above, the physical network database 333 is characterized by a schema. Figure 7 is an ORM diagram conceptually illustrating the PNM schema. The PNM schema is based on the

metashema described above with reference to Figure 5. The schema includes several object types for defining records in the physical model database 333. Referring to Figure 7, the object types include: device 701, group 702, task 703, category 704, and bitmap 705. The device object type 601 is used to represent the devices in the network, and the group object type 702 is for representing groups of devices. The task object type 703 is for representing the tasks which may be performed, and the category object type 704 is for representing categories of tasks. The bitmap object type 705 is for representing displayable bitmaps of devices, groups, tasks, and categories.

As illustrated by Figure 7, various device types 706 can be defined by the user. Each device type 706 can have multiple devices 701 associated with it; however, each device 701 can be of only one device type 706. Each device 701 can have one or more tasks 703 associated with it, and a task may be performable upon (or by) more than one device. If a device has a task, then that task is performable taking the device as a parameter. Each group 702 can have both devices 701 and tasks 703 as members. If a task is a member of a particular group, then that task may take as a parameter any device which is a member of that group. A group 702 can be a specialization of a device type 706 (i.e., a group can represent a particular type of device). A device 701 can be a member of more than one group 702. Groups 702 can be defined by the user based on arbitrary criteria and can be overlapping. Each category 704 has at least one task 703 as a member. As with groups, categories 704 can also be defined by the

user and can be arbitrary. Devices are represented by two bitmaps 705, an active bitmap to indicate that the device is on-line, and an inactive bitmap to indicate that the device is off-line. Each task 703 and each category 704 is also represented by a bitmap 705.

D. View Generator

The view generator 304 provides a user-definable listing of devices in the network 10 and available tasks, which may be displayed in the device window 201 and the task window 202 (see Figure 2A). The LAN Administrator can arrange devices in different ways to provide the most useful presentation of network organization. In particular, the user interface provide capability for "drag-and-drop" maintenance of groups, group membership, and devices. A facility to expand and collapse portions of the device tree is also provided. The view generator 304 also provides capability to: show both historical or real-time information about the devices on the network; show group membership; filter the devices and groups to select only certain devices or groups for display; and, expand and collapse the displayed portions of the tree structure of devices/groups or tasks/categories.

In one embodiment of the present invention, illustrated in Figure 9, the view generator 304 provides for two views to be displayed in tree-hierarchy form, a logical group view and a task view. In this embodiment, the view generator 304 includes a logical group view generator 341, a task view generator 342, an object filter module 344, and a view generator API 346 driving the group view generator 341, and the task view generator 342. The view generator 304 includes

API functions related to the generation of tree views and is logically coupled to a tree generator 345. Various other view generators 343 may also be included for generating different types of displays.

The view generator API 346 allows a client application to request that a logical view be displayed, and which type of view is to be displayed. Means is also provided for the maintenance of groups, group membership, and devices. The client application is notified of changes in the selection state, and can query the current selection state. The client application can search for a device in the list by name, group membership, or both. The search can be repeated to find multiple occurrences of a device in the tree. Client applications can also specify a filter to select only certain devices or groups be displayed.

The logical group view generator 341 populates the tree-structure for display in the device window 201 of the logical view 200. A logical group is simply a collection of devices. The logical group view generator 341 fills an outline for display within the device window 201 with a list of devices grouped according to their group memberships. The group view generator 341 obtains group definitions from the physical model database 333, while device information is obtained from the discovery manager 301. This information may be real time, historical, or both, depending on the type of display requested by the client. The devices and groups are then filtered according to user-provided criteria, leaving only those devices and groups requested. The remaining information is then placed in the outline for display. The tree generator 345 generates the

graphics functions required to display the outline in the form of a tree hierarchy. Various methods and products are known in the art for performing the function of the tree generator 345.

In the device window 201, a top level of the tree-structure will contain a line for each defined group. Expanding a line (e.g., by double-clicking with the mouse) will reveal, at the next level, the individual members of the group. Note that a device may belong to more than one group. Two classes of logical groups are provided for: 1) device types, 2) and user-created groups. Device types are predefined logical groups that correspond to physical device types. The discovery modules 312 can automatically create these groups and assign group membership. User-created groups are created by the LAN administrator who assigns group membership.

The Task View Generator 342 populates the tree-structure for display in the task window 202 of the logical view 200. In the preferred embodiment, all tasks that can be performed on a selected device in the device window 201 are displayed in the task window 202. The top level of the outline contains the task categories of a selected device or group. Expanding a category will reveal, at the next level, the actual tasks that are available. Users may create task categories and tasks within any predefined or user-defined category. In one embodiment, if the current selection is a device, the displayed available tasks are both those tasks that are directly assigned to the selected device and all tasks that are assigned to all groups of which the device is a member. If the current selection is a group, the

displayed available tasks are those tasks that are assigned directly to the selected group. Further, if multiple items are selected, the displayed available tasks are the intersection of all tasks that are assigned directly to all selected devices, all tasks that are assigned directly to all selected groups, and all tasks that are assigned to all groups of which the selected devices are members. As with the group views, the tree generator 345 generates the graphics functions required to display the tasks and categories in the form of a tree hierarchy.

The other view generators 343 may be included to generate other alternative views of the network. Alternative views might include a schematic display of segments, such as that shown in Figure 8, or a geographic layout of network components. A geographic view, for example, may be implemented by combining discovered device information with grid coordinates corresponding to a floor plan of a particular building or complex.

The Object Filter Module 344 is used to reduce the logical view data down to only that information which the client application wishes to display, as mentioned above. For each group and device displayed, that device will be compared to the criteria of the filter and displayed only if there is a match.

The core services 300 also include a logical view database which provides storage and retrieval of information about groups, such as group names, the bitmap to be displayed when a given group is displayed, and members of the group. In the preferred embodiment,

the logical view database is included in the physical model database 333 for data consistency.

E. Task Manager

The task manager 305 performs two main functions:

1) maintaining knowledge of all executable tasks in the network and the devices upon which such tasks can be operated, and 2) initiating tasks in response to user commands entered via the control panel. A task consists essentially of an atomic script and any associated parameters. A parameter associated with a task may be a device upon which a task will be performed. Tasks include functions for troubleshooting, monitoring, and reporting on devices.

In determining the executable tasks in the network and the devices on which such tasks can be performed, the task manager 305 makes use of the PNM schema described with reference to Figure 7. Recall that each device can have one or more tasks associated with it; that if a device has a task, then that task is performable taking that device as a parameter; that each group can have both devices and tasks as members; and, that if a task is a member of a particular group, then that task may take as a parameter any device which is a member of the same group. Thus, tasks are linked to devices and groups of devices. The task manager 305 examines these links to determine the available tasks for particular devices and groups. In the preferred embodiment, available tasks are stored in the physical model database 333.

As will be discussed below, the task manager 305 can provide a display, in response to a user's selection of one or more devices or

groups, showing the effective tasks associated with the selected devices or groups. A user may initiate a task by, for example, selecting a device or group and then double-clicking on an available (displayed) task. Tasks may also be defined by the user, and individual tasks may be combined by the user to form compound tasks.

The function of maintaining knowledge of all executable tasks in the network can be broken down into four sub-functions: 1) calculating tasks for a device or group which has been selected via a user input; 2) calculating tasks for a group; 3) calculating tasks for a device; and, 4) calculating tasks of a component (device). With regard to the first sub-function, a user input selecting one or more devices or groups will cause the Task Manager 305 to invoke an API call to the link in the physical model database 333 that associates the selected devices or groups with their effective tasks. Figure 12 illustrates the steps for calculating the tasks for a selection (device or group). The value Effective Tasks, which is initially null (step 1201), represents all effective tasks for the selected device or group. For each group that is selected (step 1204), the effective tasks for the group, Tasks for Group, is calculated (step 1202), and Effective Tasks is then updated to be the intersection of Effective Tasks with Tasks for Group (step 1203). Next, for each device that is selected (step 1207), the effective tasks for the device, Tasks for Device, is calculated (step 1205), and Effective Tasks is updated to be the intersection of Effective Tasks with Tasks for Device (step 1206). The value Effective Tasks is then returned (step 1208).

Figure 13 illustrates the steps for calculating tasks for a group. The value Tasks for Group, which is initially null (step 1301), represents all effective tasks for a given group. Tasks for Group is unioned with the effective tasks (Tasks for Group) for a "current group" to generate a new value of Tasks for Group (step 1302). Next, the current group is updated to be the parent of the current group (step 1303), and the previous step (step 1302) is repeated until the current group is the root (top level of the tree) (step 1304). The value Tasks for Group is then returned (step 1305).

Figure 14 illustrates the steps for calculating the tasks for a given device. The value Tasks for Device, which is initially null (step 1401), represents all effective tasks for a given device. For each group of which the device is a member (steps 1402, 1405), the effective tasks for that group, Tasks for Group, is calculated (step 1403), and then Tasks for Device is updated to be Tasks for Device unioned with Tasks for Group (step 1404). Next, the effective tasks for all components of the selected device, Component Tasks, is calculated (step 1406). Tasks for Device is then updated to be Tasks for Device unioned with Component Tasks (step 1407). Next, Tasks for Device is updated to be Tasks for Device unioned with all tasks which are assigned to the given device (step 1408). Finally, the value Tasks for Device is returned (step 1409).

Figure 15 illustrates the steps for calculating Component Tasks. The value Tasks for Component, which is initially null (step 1501), represents all effective tasks for a component of a given device. For

each device which is a component of a given device (steps 1502, 1505), Tasks for Device is calculated (step 1503), and Tasks for Component is updated to be Tasks for Component unioned with Tasks for Device (step 1504). The value Tasks for Component is then returned (step 1506).

Thus, a method and apparatus for providing management services for a computer network has been described. The management services are designed from a flexible, device-oriented perspective in order to provide the user with information on the layout of the network, tasks that can be performed, and the devices on which each particular task can be performed. The services further provide the user with customizable ways of viewing the layout of the network. Although the present invention has been described with reference to specific exemplary embodiments, it will be evident that various modifications and changes may be made to these embodiments without departing from the broader spirit and scope of the invention as set forth in the claims. Accordingly, the specification and drawings are to be regarded in an illustrative rather than a restrictive sense.

CLAIMS

What is claimed is:

1. A computer-implemented method of managing a computer network, the network including a plurality of devices, each of a plurality of tasks being performable upon at least one of the devices, the method comprising the steps of:

determining a present state of the network, the present state of the network including a present configuration of the network;

storing data representing the present state of the network in a database;

determining for each of the devices the tasks which may be performed; and

generating a display corresponding to the present state of the network, wherein the display includes an association of the devices with the tasks performable on the devices.

2. A computer-implemented method according to claim 1, further comprising the step of organizing the devices into a plurality of groups.

3. A computer-implemented method according to claim 2, further comprising the step of identifying, for each of the groups, the tasks that are performable upon every device in said group.

4. A computer-implemented method according to claim 1, further comprising the step of, upon receiving a user input selecting at least one device, identifying on the display which of the tasks are performable by said at least one device.

5. A computer-implemented method according to claim 2, further comprising the step of identifying, for each of the groups, the tasks that are performable upon every device in said group.

6. A computer-implemented method according to claim 1, further comprising the step of initiating one of the tasks displayed on the display in response to a user input selecting said one of the tasks.

7. A computer-implemented method according to claim 1, further comprising the steps of:

identifying, in response to a user query, devices of a particular type that are present in the network; and

generating the display such that the devices of the particular type are identified on the display.

8. A computer-implemented method according to claim 1, wherein the step of generating the display comprises the step of generating a hierarchical representation of the devices.

9. A computer-implemented method according to claim 8, wherein the step of generating the display comprises the step of generating a hierarchical representation of a subset of the tasks.
10. A computer-implemented method according to claim 1, wherein the step of generating the display comprises the step of generating a schematic representation of the devices.
11. A computer-implemented method according to claim 1, wherein the step of generating the display comprises the step of generating a geographical representation of the devices.
12. A computer-implemented method according to claim 1, further comprising the steps of:
 - storing data representing a past state of the network; and
 - providing a display corresponding to a comparison of the past state of the network and the present state of the network.
13. A computer-implemented method according to claim 1, wherein the data about a present configuration of the network includes information relating to the types of devices in the network and interconnections between the devices in the network.
14. A computer-implemented method of managing a computer network, the network including a plurality of devices, each of a

plurality of tasks being performable upon at least one of the devices, the method comprising the steps of:

gathering data about a present state of the network, the data including information about a present configuration of the network and the tasks performable upon the devices in the network;

storing the data in a database representing a network state; and

generating a display of the present state of the network, the display including a first portion displaying a representation of the network state, wherein the representation is displayable as a tree structure including symbols representing the devices, the display further including a second portion, the second portion displaying, for a device or group of devices selected from the first portion, the tasks performable upon said device or group of devices selected.

15. A computer-implemented method according to claim 14, wherein in the first portion, the devices are displayed organized into device groups.

16. A computer-implemented method according to claim 14, wherein in the second portion, the tasks are displayed organized into task categories.

17. A computer-implemented application for managing a computer network, the computer network including a plurality of devices, the

application implemented in one of the devices, the application comprising:

- a discovery manager gathering data about a present configuration of the network;

- a database coupled to the discovery manager, the database storing the data, the database representing a network state;

- a task manager coupled to the discovery manager, the task manager for determining and maintaining task information, the task information including the tasks performable upon the devices in the network, the task information further including associations of each of the tasks with the devices upon which said tasks can be operated; and

- a view generator coupled to the discovery manager, the view generator providing a display to a user corresponding to the network state and the task information.

18. A computer-implemented application according to claim 17, wherein the data about a present configuration of the network includes information about the types of devices in the network, the quantity of each type of device present in the network, and the interconnections between the devices in the network.

19. A computer-implemented application according to claim 17, wherein the display may indicate physical relationships or logical relationships between the devices.

20. A computer-implemented application according to claim 17, wherein the display includes a hierarchical display of the devices.
21. A computer-implemented application according to claim 17, wherein the display includes a schematic display of the devices.
22. A computer-implemented application according to claim 17, wherein the display includes a geographic display of the devices.
23. A computer-implemented application according to claim 17, wherein the view generator further provides a display of the tasks performable upon a selected device.
24. A computer-implemented application according to claim 23, further providing means for the user to initiate one of the displayed tasks by applying a user input based on the displayed task information.
25. A computer-implemented application according to claim 23, wherein the devices may be categorized into a plurality of groups, wherein for each of the groups, the task manager further identifies the tasks that are performable upon every device in said group.
26. A computer-implemented application according to claim 25, wherein one or more of the groups are defined by a user.

27. A computer-implemented application according to claim 25, wherein the tasks displayed are associated with particular devices or particular groups of devices.
28. A computer-implemented application according to claim 17, wherein the tasks may be organized into a plurality of categories, each of the categories comprising at least one of the tasks.
29. A computer-implemented application according to claim 28, wherein one or more of the categories is defined by a user.
30. A computer-implemented application according to claim 17, the discovery manager including a plurality of modules, each of the modules for identifying devices with a unique set of attributes.
31. A computer-implemented application according to claim 17, wherein the database further includes data representing a past configuration of the network.
32. A computer-implemented application according to claim 31, wherein the view generator generates a display corresponding to a comparison of the past configuration of the network to the present configuration of the network.

33. A program storage device readable by a machine, the storage device tangibly embodying a program of instructions executable by the machine to perform method steps for managing a computer network, the computer network including a plurality of devices coupled by a plurality of connections, the method steps comprising:

gathering data about a present state of the network, the data including the types of devices in the network, the connections between the devices, and the tasks performable upon the devices;

storing the data in a database; and

generating a display corresponding to the data in the database, wherein the display shows an association of the devices with the tasks performable upon the devices.

34. A program storage device according to claim 33, wherein the network map may include physical relationships or logical relationships between the devices.

35. A program storage device according to claim 33, wherein the display includes any of a tree-structured, schematic, or geographical display of the devices.

36. A program storage device according to claim 33, wherein the method steps further comprise the steps of:

associating each of the devices with the tasks which are performable upon each of said devices; and

maintaining a displayable task register including the devices and the tasks which are performable upon each of said devices.

37. A program storage device according to claim 33, wherein the method steps further comprise the steps of:

associating a group of the devices with the tasks which are performable upon each of the devices in the group; and

maintaining a displayable task register including the devices in the group and the tasks which are performable upon each of said devices in the group.

38. A program storage device according to claim 36, wherein the method steps further comprise the steps of initiating one of the tasks displayed on the display in response to a user input selecting said one of the tasks.

39. A program storage device according to claim 33, wherein the method steps further comprise the steps of:

storing data representing a past configuration of the network;
and

providing a display corresponding to a comparison of the past configuration of the network and the present configuration of the network.

40. A database schema characterizing a database, the database for representing a physical model of a computer network, the computer network including a plurality of devices, the schema including a plurality of object types characterizing a plurality of objects, each of the objects representing at least one of a plurality of records of the database, the object types comprising:

a device object type for representing the devices;

a task object type for representing a plurality of tasks, each of the tasks performable on at least one of the devices;

a group object type for representing a plurality of groups, wherein each group may have at least one of the devices as members, and wherein each group may have at least one of the tasks as members;

a category object type for representing a plurality of categories, wherein each of the categories has at least one of the tasks as members; and

a bitmap object type for representing a plurality of bitmaps, wherein each of the groups is represented by at least one of the bitmaps, wherein each of the tasks is represented by one of the bitmaps, and wherein each of the categories is represented by one of the bitmaps.

41. A database schema according to claim 40, wherein any of the tasks which is a member of one of the groups is performable on each one of the devices which is a member of said one of the groups.

42. A database schema according to claim 40, further comprising a plurality of device types, each of the devices being of one of the device types, each of the device types representing at least one of the devices, wherein at least one of the groups may represent at least one of the device types.

43. A method of defining a schema for a database, the database for representing a physical model of a computer network including a plurality of devices, the method comprising the step of defining a plurality of object types for characterizing a plurality of objects, each of the objects representing at least one of a plurality of records of the database, wherein the object types include:

- a device object type for representing the devices;
- a task object type for representing a plurality of tasks, each of the tasks performable on at least one of the devices;
- a group object type for representing a plurality of groups, wherein each group may have at least one of the devices as members, and wherein each group may have at least one of the tasks as members;
- a category object type for representing a plurality of categories, wherein each of the categories has at least one of the tasks as members; and
- a bitmap object type for representing a plurality of bitmaps, wherein each of the groups is represented by at least one of the

bitmaps, wherein each of the tasks is represented by one of the bitmaps, and wherein each of the categories is represented by one of the bitmaps.

44. A method according to claim 43, wherein any of the tasks which is a member of one of the groups is performable on each one of the devices which is a member of said one of the groups.

45. A method according to claim 43, further comprising a plurality of device types, each of the devices being of one of the device types, each of the device types representing at least one of the devices, wherein at least one of the groups may represent at least one of the device types.

46. A computer-implemented method of providing information on a computer network including a plurality of devices, each of a plurality of tasks being performable upon at least one of the devices, the method comprising the steps of:

- generating a display having a first area corresponding to the devices and a second area corresponding to the tasks;

- displaying in the first area a representation of a subset of the plurality of devices;

- accepting a user input selecting the representation; and

- in response to the user input, displaying in the second area information indicating which of the tasks are performable upon each device of the subset of the plurality of devices.

47. A computer-implemented method according to claim 46, wherein the step of displaying a representation comprises the step of displaying a bitmap of one of the devices or of a group of the devices.

48. A computer-implemented method according to claim 47, wherein the step of accepting a user input comprises the step of accepting a user input selecting the bitmap.

49. A computer-implemented method according to claim 46, further comprising the step of determining which of the tasks are performable upon each device of the subset of the plurality of devices.

50. A computer-implemented method according to claim 46, wherein the step of displaying in the first area a representation of a subset of the devices comprises the step of displaying in the first area a first tree structure representing the subset of the plurality of devices.

51. A computer-implemented method according to claim 50, wherein the step of displaying in the second area information indicating which of the tasks are performable upon each device of the subset of the devices comprises the step of displaying in the second area a second tree structure representing the tasks that are performable upon each device of the subset of the plurality of devices.

52. A program storage device readable by a machine, the storage device tangibly embodying a program of instructions executable by the machine to perform method steps for providing information on a computer network including a plurality of devices, each of a plurality of tasks being performable upon at least one of the devices, the method steps comprising the steps of:

generating a display having a first area corresponding to the devices and a second area corresponding to the tasks;

displaying in the first area a representation of a subset of the plurality of devices;

accepting a user input selecting the representation; and

in response to the user input, displaying in the second area information indicating which of the tasks are performable upon each device of the subset of the plurality of devices.

53. A program storage device according to claim 52, wherein the method steps further comprise the step of displaying a representation comprises the step of displaying a bitmap of one of the devices or of a group of the devices.

54. A program storage device according to claim 53, wherein the method steps further comprise the step of accepting a user input comprises the step of accepting a user input selecting the bitmap.

55. A program storage device according to claim 52, wherein the method steps further comprise the step of determining which of the tasks are performable upon each device of the subset of the plurality of devices.

56. A program storage device according to claim 52, wherein the method steps further comprise the step of displaying in the first area a representation of a subset of the devices comprises the step of displaying in the first area a first tree structure representing the subset of the plurality of devices.

57. A program storage device according to claim 56, wherein the step of displaying in the second area information indicating which of the tasks are performable upon each device of the subset of the devices comprises the step of displaying in the second area a second tree structure representing the tasks that are performable upon each device of the subset of the plurality of devices.




FIG. 1




Figure 2A

200







Figure 2B

**FIG. 3**

**FIG. 4**

**FIG. 5**




FIG. 6




FIG. 7




FIG. 8






FIG. 9


10/15


**FIG. 10**


11/15

**FIG. 11**


12/15

**FIG. 12**

**FIG. 13**

**FIG. 14**

15/15

**FIG. 15**

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US96/20104

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : G06F 13/00; 17/30; 03/00

US CL : 395/335; 614; 200.1

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 395/335; 614; 200.1; 329; 611

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

aps: network, device, interface, display

C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category* | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|-----------|--|-----------------------|
| X | US 5,471,399 A (TANAKA et al.) 29 November 1995, abstract, col. 1 line 45 to col. 2 line 46. | 1-39 |
| X | US 5,335,323 A (KOLNICK) 02 August 1994, abstract, col. 2 line 57 to col. 3 line 22. | 1-39 |
| A,P | US 5,553,226 A (KIUCHI et al.) 03 September 1996. | 1-39 |
| X | US 5,414,812 A (FILIP et al.) 09 May 1995, abstract, col. 2 line 65 to col. 5 line 5. | 40-45 |
| X | US 5,398,336 A (TANTEY et al.) 14 March 1995, abstract, col. 2 lines 9-46. | 40-45 |
| A | US 5,434,791 A (KOKO et al.) 19 July 1995 | 40-45 |

☒ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

| | | |
|--|-----|--|
| * Special categories of cited documents: | *T | later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention |
| *A* document defining the general state of the art which is not considered to be of particular relevance | *X* | document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone |
| *E* earlier document published on or after the international filing date | *Y* | document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art |
| *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reasons (as specified) | *A* | document member of the same patent family |
| *O* document referring to an oral disclosure, use, exhibition or other means | | |
| *P* document published prior to the international filing date but later than the priority date claimed | | |

Date of the actual completion of the international search

19 MARCH 1997

Date of mailing of the international search report

04 JUN 1997

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer
RICHARD ELLIS

Telephone No. (703) 305-9690

Form PCT/ISA/210 (second sheet)(July 1992)*

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US96/20104

| C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT | | |
|---|---|-----------------------|
| Category* | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
| X,E | US 5,604,892 A (NUTTALL et al.) 18 February 1997, abstract, col. 1 line 65 to col. 2 line 25. | 40-45 |
| A,P | US 5,504,921 A (DEV et al.) 02 April 1996. | 40-45 |
| X | US 5,428,730 A (BAKER et al. 27 June 1995, abstract, col. 1 line 36 to col. 2 line 20. | 46-57 |
| A,P | US 5,483,631 A (NAGAI et al.) 09 January 1996 | 46-57 |
| X | US 5,452,415 A (HOTKA) 19 September 1995, abstract, col. 1 line 29 to col. 2 line 53. | 46-57 |

Form PCT/ISA/210 (continuation of second sheet)(July 1992)*

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US96/20104

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This international report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. This International Search Authority has found 3 inventions claimed in the International Application covered by the claims indicated below:

This application contains the following inventions or groups of inventions which are not so linked as to form a single inventive concept under PCT Rule 13.1. In order for all inventions to be searched, the appropriate additional search fees must be paid.

Group I, claim(s) 1-39, drawn to a method of managing a computer network.
Group II, claim(s) 40-45, drawn to a database schema.
Group III, claim(s) 46-57, drawn to a user interface.

1. ☒ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☒ The additional search fees were accompanied by the applicant's protest.
☐ No protest accompanied the payment of additional search fees.

Form PCT/ISA/210 (continuation of first sheet(1))(July 1992)*